

SERIE 2 120

DB452
NORDIC WHITE



DB551
CORNSILK



DB412
GRAND OAK



DB372
CASTLE BROWN



DB160
URBAN SILVER GREY



DB162
SKY GREY



SUBJECT	MAIN PARAMETER	REFERENCE
Thickness	2.0 mm	ISO 24364
Wear Layer	Class 22+/0.20 mm	ISO 24340
Packaging Unit	22 Planks / box = 4.94m ²	
Plank Size	184.15 x 1219.2 x 2.0 mm [W x L x T]	
Application	Domestic General	ISO 10870
Guarantee	10 year limited residential	
TECHNICAL DATA		
Name	deZIGN SERIES 120	
Type of flooring	Heterogeneous PVC floor covering	ISO 10582
Classification	Class 22+	ISO 10874
Component	PVC plasticizer Stabilizer CaCO ₃	
Finish	Regular Emboss	
Structure	Composite (Wear Layer: 0.2 mm, Print film: 0.07 mm, Back Layer: 1.73 mm)	ISO 24342
Size	Deviation ≤0.15% of nominal length up to 0.5mm maximum	ISO 24342
Squareness, mm	≤400mm deviation≤0.25; >400mm, ≤0.35>400mm, ≤0.35	ISO 24342
Straightness, mm	≤400mm deviation≤0.25; >400mm, ≤0.35>400mm, ≤0.35	ISO 24346
Overall thickness, mm	Average: 2.0mm + 0.13/-0.10mm, individual value: average +/- 0.15mm	ISO 20340
Wear layer thickness, mm	0.20mm +13%/-10%	
Surface treatment	≤0.12%	EN 434
Bevelled edges	≤1.12mm	EN 434
Colour Fastness	Double PU coating	
Dimensional Stability	Grade 6	ISO 105-B02
Total Mass Per Unit Area	3.444 kg/m ² + 13%/-10%	ISO 24343-1
Residual Indentation (average)	≤0.10 mm	EN 433
Reaction to fire	Bfl-s1 Classification	EN 13501-1
Chemical resistance	No effect	EN 423
Effect of a castor chair	15 000 cycle no delamination (Appearance Slight Change)	ISO 4918
Slip Resistance	DS	EN 13893
	ΔLw = 11dB CΔ = -6dB	EN ISO 10140-3
Hardness	60°+/-5°	EN660-2
Abrasion Resistance	Group T	EN 660-2
Toxicity	Non-toxic, no heavy metals	EN 717-1
Formaldehyde Emission	EO	EN 717-1
Recycled Materials	No	
INSTALLATION & MAINTENANCE GUIDELINES		
Installation	Adhere to manufacturers installation guidelines as set out on packaging.	
Cleaning & Maintenance	Sweep regularly. Clean with NON-ABRASIVE detergent using a micro-fiber mop.	
Caution	Avoid exposure to direct sunlight.	



LVT Glue Down

